


Technical Parameters

1. Electrical Rating: 0.1A 125/250VAC  
3A/12VDC; 0.1A/48VDC
2. Electrical lifetime: 100 000
3. Mechanical lifetime: 100 000
4. Contact Resistance: ≤100mΩ
5. Operating force: 1.0~3.5N
6. Pretravel: 0.3~1.0mm
7. Withstand Voltage: Feet and Feet 750V/5S/5mA  
Feet and Shell 1500/5S/5mA
8. Insulation Resistance: ≥100MΩ (Test Voltage 500VDC)
9. Proof Tracking Index (PTI): 175V
10. Ambient temperature: 125°

Circuit diagram



Waterproof grade: IP67

1	Rubber shell	PA66
2	seal ring	Silica gel
3	base	Brass+PA66
4	According to sincerity	POM
5	Contact moving plate	C5191+AgNi10
6	Strut	SUS301-H

广东星坤科技股份有限公司

生	日期	units: mm	DSND	DATE	SCALE: N/A	MODEL TYPE: Microswitch		
ΔX	日期	tolerance: X.X ±0.2mm	DWN	DATE	VIEW:	PART NO.:		
ΔX	日期	X.XX ±0.1mm	CHKD	DATE	UNIT: mm/in	DWG NO.: DF1-136UNY-1		
ΔX	日期	X.XXX ±0.05mm	APPD	DATE	SIZE: A4			
MARK	DESCRIPTION	UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT: 1.0g	SHEET: 1/1	REVISION: A0
文件工程章		REVISIONS						
		DATE	REVISED	APPROVED				
		www.xk-dg.cn	www.helloxkb.com		www.helloxkb.cn			

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)