



Technolo Request:

- 1.Outlook:  
NO burr,no hurt.
- 2.Electronic performance:  
a:Insulation resistance:  
Above DC500V/100MΩ;  
b:Endure voltage:  
AC500V at 1 minute;  
c:Contact resistance:  
Under 30MΩ;
- 3.Insertion fore & withdrawal force;0.3-3kgf.
- 4.Salt spray test :48H.
- 5.Meet RoHS.
- 6.Remark \* is important specification

	MATERIAL	PLATING
Terminal	phosphor bronze	NI
Fork hook tube	H65	NI
Plastic	Pbt	Black

广东星坤科技股份有限公司

生	日期
發	日期
Δx	
MARK	
文件	工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGULAR				±5°
L ≤ 4				±0.2
4 < L ≤ 16				±0.3
16 < L ≤ 63				±0.4
L > 63				±0.5

DSND	DATE	SCALE: N/A	MODEL TYPE: DC PIUG
DWN	DATE	VIEW:	PART NO.: DT-2306530
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
KKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)