



SPECIFICATIONS:

- 1.ELECTRICAL CHARACTERISTICS:1-1.RATING:DC24V 6A
1-2.CONTACT RESISTANCE:30m2MAX.(INITIAL)
1-3.DIELECTRIC WTHSTANDING VOLTAGE:500V AC FOR ONE MINUTE
1-4.INSULATION RESISTANCE:100MQ MIN. MEASURED BY 500V DC
- 2.MECHANICAL CHARACTERISTICS:
2-1.Plug it into the mother socket 3 times INSERTION FORCE:0.3~3.0 KGF
2-2. Plug it into the mother socket 5000 times INSERTION FORCE:0.3~3.0 KG
- 3.SALT FOG:24 Hours
- 4.FOR REFLOW SOLDERING LEAD-FREE PROCESS
5. * REPRESENT CRITICAL DIMENSIONS.

	MATERIAL	PLATING
TERMINAL 1	Phosphor bronze	NI
Fork hook tube	C3604	NI
plastic	PBT	Black

广东星坤科技股份有限公司

生 日期
發 日期

ΔX
MARK 文件工程章

REVISIONS

DESCRIPTION DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: DC PLUG
DWN	DATE	VIEW:	PART NO.: DT-2355525
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
KKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)