



(Ø3.50mm 4 POLE PLUG DETAIL DRAWING)

- NOTES:
 1. REFER TO GWS025, REQUEST OF THE SPECIFICATION:
 (1) CONTACT RESISTANCE: 50mΩ MAX.;
 (2) INSULATION RESISTANCE: 100MΩ MIN.;
 (3) DIELECTRIC WITHSTANDING: 500V AC MIN.;
 (4) DURABILITY: SEE TABLE B;
 (5) CONNECTOR MATING FORCES: 2.94~29.4N (0.3~3.00Kgf);
 (6) CONNECTOR UNMATING FORCES: 2.94~29.4N (0.3~3.00Kgf);

	MATERIAL	PLATING
terminal 1	Phosphor Bronze	Gold
terminal 2	Phosphor Bronze	Gold
terminal 3	Phosphor Bronze	Gold
terminal 4	Phosphor Bronze	Gold
terminal 5	Phosphor Bronze	Gold
terminal 6	Phosphor Bronze	Gold
plastic	High Temp. Thermoplastic	

广东星坤科技股份有限公司

生效	日期
ΔX	
ΔX	
ΔX	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	REVISIONS
文件	工程				

MARK	DESCRIPTION	DATE	REVISED	APPROVED	REVISIONS

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	2.5 PHONE JACK
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.: PJ-2065-SMT
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT: 1.0g
			SHEET: 1/1
			REVISION: A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)