


1. Rating: DC 30V 0.5A;
2. Contact resistance: $\leq 0.03\Omega$;
3. Insulation resistance: $\geq 100m\omega$ (dc250v)
4. Withstand voltage: 500vac;
5. Insertion and extraction force: 3-30n;
6. Life test: 5,000 cycles

	MATERIAL	PLATING
terminal 3	Phosphor Bronze	tin
terminal 4	Phosphor Bronze	tin
terminal 5	Phosphor Bronze	tin
plastic	Pbt	



广东星坤科技股份有限公司

生效日期

文件工程章

日期

REVISIONS

www.helloxk.cn www.helloxk.com www.helloxk.cn

ANGLAR $\pm 5^\circ$
 $L \leq 4$ ± 0.2
 $4 < L \leq 16$ ± 0.3
 $16 < L \leq 63$ ± 0.4
 $L > 63$ ± 0.5
 UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.: PJ-318-X
APPD		DATE		SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET
				1.0g	1/1
				REVISION	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)