


**SCHMATIC**



**SPECIFICATION**

1. Rating: DC 30V 0.5A;
2. Contact resistance:  $\leq 50\text{m}\Omega$ ;
3. Insulation resistance:  $\geq 100\text{M}\Omega$  (DC250V);
4. Withstand Voltage: 500VAC;
5. Insertion and extraction force: 3-25N;
6. life test: 5,000 cycles.

	MATERIAL	PLATING
terminal 1	copper alloy	silver
terminal 2	copper alloy	silver
terminal 3	copper alloy	silver
terminal 4	copper alloy	silver
plastic	PBT	

广东星坤科技股份有限公司

生效日期

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

文件工程章

DSND		DATE	SCALE: N/A	MODEL TYPE: 6.5 PHONE JACK
DWN		DATE	VIEW:	PART NO.:
CHKD		DATE	UNIT: mm/in	DWG NO.: PJ-623AX-X
APPD		DATE	SIZE: A4	WEIGHT SHEET REVISION
XKB INDUSTRIAL PRECISION CO., LIMITED				1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)