



**SPECIFICATION**

Contact Rating: 50mA, 12V DC  
 Contact Resistance: 100mΩ max  
 Insulation Resistance: 100mΩ min.500V DC  
 Dielectric Strength: 250V AC/1minute  
 Travel: 0.25mm  
 Operating Temp: -20℃~+70℃  
 Storage Temp: -30℃~+80℃

PAPT NO	TC-1101DE-X-X
Operating Force	B:160gf C:260gf
Height	code-x



code-x	H
A	4.3
B	4.8
C	5.0
D	5.3
E	5.5
F	6.0

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	2	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	LCP	—	—
②	Cover	—	1	Spcc	Plating Nickel	—
①	Keystake	—	1	Pa46	—	—

广东星坤科技股份有限公司

生效	日期
ΔX	日期
ΔX	日期
ΔX	日期

文件工程章

REVISIONS	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE:		
		DWN	DATE	VIEW:	TACT SWITCH		
		CHKD	DATE	UNIT: mm/in	PART NO.:		
		APPD	DATE	SIZE: A4	DWG NO.:		
		XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT	SHEET	REVISION
					1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)