



SPECIFICATION
 Contact Rating: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min. 500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 1.2mm
 Operating Temp: -30° ~ +85°
 Storage Temp: -30° ~ +80°

PAPT NO	TC-1117D-X
Operating Force	A:120gf B:160gf C:260gf
Height	H:5.0

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
①	Terminal	2	Brass (0.30t)	Plating silvering		
②	Base	1	Pa46			
③	Keystone	1	Silica gel			

广东星坤科技股份有限公司

生效日期

文件工程章

DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	TACT SWITCH
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.:
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT: 1.0g
			SHEET: 1/1
			REVISION: A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)