



**SPECIFICATION**

Contact Rating: 50mA, 12V DC  
 Contact Resistance: 100mΩ max  
 Insulation Resistance: 100mΩ min. 500V DC  
 Dielectric Strength: 250V AC/1minute  
 Travel: 0.25mm  
 Operating Temp: -40°C ~ +90°C  
 Storage Temp: -30°C ~ +80°C

PAPT NO	TC-111A-X
Operating Force	A:130gf B:200gf C:300gf D:500gf
Height	H:6.65



**P.C.B Mounting hole dimensionis**



It is suggested to use P.C.B Board of 1.6mm thick

ITEM	PAPT NAM	TER,NC	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	---	2	Brass (0.30t)	Plating silvering	---
④	Contact	---	1	F.ag/SUS	Natural	---
③	Base	---	1	Pa46	---	---
②	Cover	---	1	Brass	Plating Nickel	---
①	Keystake	---	1	Steel ball	---	---

广东星坤科技股份有限公司

生效日期

文件工程章

REVISIONS	DATE	REVISED	APPROVED	DESCRIPTION

DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.: TC-111A-X
APPD		DATE		SIZE: A4	WEIGHT: 1.0g
XKB INDUSTRIAL PRECISION CO., LIMITED				SHEET: 1/1	REVISION: A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)