



- NOTE:**
1. Rating: DC 5V 10mA
 2. Contact Resistance: 100mΩMAX
 3. Insulation Resistance: 100mΩMIN
 4. Soldering Temper: 260±5°/5s
 5. Mechanical Life: 100,000 cycles
 6. Ever Portion 80±50gf
 7. Push Portion 205±80gf
 8. Travel: -24° 0° +24°

A向24°a与b
 B向24°a与d
 C向150g
 a与c通

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	5	Phosphor Bronze	Plating silver		
④	Base	1	Lcp			
③	Spring	1	Sus	Natural		
②	Cover	1	Sus	Natural		
①	Keystake	1	Ppa			

广东星坤科技股份有限公司

生 效 日期

文件工程章

www.helloxkb.com www.helloxkb.com www.helloxkb.com

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: MULTI-FUNCTIONAL SWITCH
					ANGLAR ±5°	DWN	DATE	VIEW:	PART NO.:
					L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm/in	DWG NO.:
					4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	TM-2011
					16 < L ≤ 63 ±0.4	XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
					L > 63 ±0.5				SHEET 1/1
									REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)