



**NOTE:**

- 1.Rating: DC 5V 10mA
- 2.Contact Resistance:100mΩMAX
- 3.Insulation Resistance:100mΩMIN
- 4.Soldering Temper: 260±5°/5s
- 5.Mechanical Life: 100,000 cycles
- 6.Ever Portion 80±50gf
- 7.Push Portion 205±80gf
- 8.Travel:-24° 0° +24°

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	5	Phosphor Bronze	Plating silver		
④	Base	1	Lcp			
③	Spring	1	Sus	Natural		
②	Cover	1	Sus	Natural		
①	Keystake	1	Ppa			

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
生					ANGLAR ±5°
效					L ≤ 4 ±0.2
					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	MULTI-FUNCTIONAL SWITCH
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.:
			TM-2011A
			WEIGHT
			SHEET
			REVISION
			1.0g
			1/1
			A0

XKB INDUSTRIAL PRECISION CO., LIMITED

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)