



| PART NO | |
|-----------|-----------|
| TM-8764-1 | TM-8764-2 |
| | |

NOTE:
 Rating:DC 30V 0.1A
 Operating Force:30±10gf
 Lifetime:100,000 Cycles
 Operating Force:25±10gf

| ⑤ | Contact Spring | — | 1 | Phosphor Bronze | Plating silver | — |
|------|----------------|--------|-----|-----------------|----------------|--------|
| ④ | Terminal | — | 4 | Phosphor Bronze | Plating silver | — |
| ③ | Base | — | 1 | Lcp | — | — |
| ② | Cover | — | 1 | Sus | Natural | — |
| ① | Keystake | — | 1 | Nylon | — | — |
| ITEM | PAPT NAMF | TER.NO | QTY | MATERIAL | FINISHING | REMARK |

广东星坤科技股份有限公司

生效日期

文件工程章

| REVISIONS | UNSPECIFIED TOLERANCES | DSND | DATE | SCALE: N/A | MODEL TYPE: |
|------------------------|------------------------|---------------------------------------|------|-------------|--------------------|
| DATE | DATE | DWN | DATE | VIEW: | DETECT SWITCH |
| REVISED | DATE | CHKD | DATE | UNIT: mm/in | PART NO.: |
| APPROVED | DATE | APPD | DATE | SIZE: A4 | DWG NO.: TM-8764-X |
| UNSPECIFIED TOLERANCES | | KXB INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT |
| | | | | | 1.0g |
| | | | | | SHEET |
| | | | | | 1/1 |
| | | | | | REVISION |
| | | | | | A0 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)