



Specifications
 CONTACT RATING:0.1A 30 VDC
 MECHANICAL ELECTRICAL LIFE:50,000 cycles
 CONTACT RESISATNCE:150Ωmax. initial
 INSULATION RESISATNCE:100Ωmin. 100VDC
 OPERATING TEMPERATURE:-20℃to+70℃
 DIELECTRIC STRENGTH:100 volts AC 60 HZ
 PACKAGING:Bulk

⑥	Spring		1	Sus	Natural	
⑤	Contact Spring	—	1	Phosphor Bronze	Plating silver	—
④	Terminal	—	2	Phosphor Bronze	Plating silver	—
③	Base	—	1	Nylon		—
②	Cover	—	1	Nylon		—
①	Keystake	—	1	Nylon		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

					units: mm	DSND		DATE		SCALE: N/A	MODEL TYPE: DETECT SWITCH	
					tolerance:	DWN		DATE		VIEW:	PART NO.:	
ΔX					X.X ±0.2mm	CHKD		DATE		UNIT: mm/in	DWG NO.:	
ΔX					X.XX ±0.1mm	APPD		DATE		SIZE: A4	TM-W-09	
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX ±0.05mm	UNSPECIFIED TOLERANCES				WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn						XKB INDUSTRIAL PRECISION CO.,LIMITED				1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)