



RECOMMENDED PCB LAYOUT
TOP VIEW (Tol:±0.05)

NOTES

- CONTACT CURRENT RATING:1.0A(SIGNAL PIN2,3,4);2.0A(POWER PIN1,5).
- CONTACT RESISTANCE:30mΩ MAX.;
- INSULATION RESISTANCE:1000MΩ MIN.;
- DIELECTRIC WITHSTANDING: 100V AC MIN.;
- DURABILITY:5,000 CYCLES MIN.;
- CONNECTOR MATING FORCES:2.55Kgf)MAX.;
- CONNECTOR UNMATING: FORCES: 2~25N(0.20~2.55Kgf);

ITEM	PAPT NAME	QTY	MATERIAL	FINISHING
①	Shell	1	SUS304R-1/2H	Ni Plating T=0.3mm (3u)
②	Terminal	5	Phosphor Bronze C5191R-EH	Au/Ni Plating T=0.2mm (1u)
③	Housing	1	HI-TEMP_PLASIC UL 94V-0	BLACK

广东星坤科技股份有限公司

生效日期

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

文件工程章

REVISIONS
www.helloxb.com www.helloxb.com www.helloxb.com

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	MICRO USB
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.:
			U-E-M5SS-W-4
			WEIGHT
			1.0g
			SHEET
			1/1
			REVISION
			A0

XKB INDUSTRIAL PRECISION CO.,LIMITED

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)