

SECT B-B



U261-24XN-4BS65-PC-1P




XKB CONNECTIVITY

P/N	R/C
U261-24XN-4BS65-PC-1P	

C TYPE PLUG: PCB:

- A1+A12+B1+B12 — GND
- A4+A9+B4+B9 — VCC
- A5 — A5(CC1)
- A6+B6 — A6+B6(D+)
- A7+B7 — A7+B7(D-)
- A8 — A8(SBU1)
- B5 — B5(CC2)
- B8 — B8(SBU2)

- 1: Au1u"
- 2: Au3u"
- 4: Au15u"
- 5: Au30u"



XKB CONNECTIVITY

REMARKS:

1.CONTACT INSERTION AND WITHDRAW FORCE:

- 1.Insertion force: 5N-20N max.
2. Withdrawal force: 8N-20N.
- 3.Durability : 10000Cycles.



2.ELECTRIC PROPERTY:

- 1.Contact current rating: 3A.
- 2.Dielectric Strength: 100V AC(RMS).
- 3.Insulation Resistance: 100 megaohms min.
- 4.Contact resistance:


40m0hms MAX.FOR VBUS,GND AND OTHER CONTACT  
50m0hms MAX.AFTER ENVIRONMENT TEST

3.AMBIENT TEMPERATURE:

- 1.Operating temperature: -55°C to +85°C.



D  
2:1



SECT A-A  
XKB CONNECTIVITY

A12	A11	A10	A9	A8	A7	A6	A5	A4	A3	A2	A1
GND	RX2+	RX2-	Vbus	SBU1	D-	D+	CC	Vbus	TX1-	TX1+	GND
GND	TX2+	TX2-	Vbus	Vconn			SBU2	Vbus	RX1-	RX1+	GND
B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12

6	Shrapnel	SUS T=0.10mm	
5	Shell	SUS T=0.15mm	Ovep-plating: Ni
4	Terminal	C7025 T=0.15mm	Ovep-plating: Au Ni/Sn
3	Latch	SUS T=0.4mm	
2	Housing	LCP	UL94-0
1	Housing Stopper	LCP	UL94-0
ITEM	DESCRIPTION	MATERIAL	REMARKS

				ANGULAR	±5°	DSND	DATE	SCALE: N/A	MODEL TYPE: 3.1 TYPE C
				L ≤ 4	±0.2	DWN	DATE	VIEW:	PART NO.:
				4 < L ≤ 16	±0.3	CHKD	DATE	UNIT: mm/in	DWG NO.:
				16 < L ≤ 63	±0.4	APPD	DATE	SIZE: A4	U261-24XN-4BS65-PC-1P
				L > 63	±0.5	UNSPECIFIED TOLERANCES			WEIGHT
				REVISIONS			XKB INDUSTRIAL PRECISION CO., LIMITED		
				UNSPECIFIED TOLERANCES			SHEET		
				UNSPECIFIED TOLERANCES			REVISION		
				UNSPECIFIED TOLERANCES			1.0g		
				UNSPECIFIED TOLERANCES			1/1		
				UNSPECIFIED TOLERANCES			A0		

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)