



**Specifications:**

规格:  
**Voltage rating:**30V AC/DC  
 额定电压: 30V AC/DC  
**Current rating:** 0.2A AC/DC(AWG#36)  
 0.3A AC/DC(AWG#34)  
 额定电流: 0.2A AC/DC(AWG#36)  
 0.3A AC/DC(AWG#34)  
**Withstanding voltage:**200V AC/minute  
 耐压电压: 200V AC/分钟  
**Temperature range:**-25℃~+85℃  
 温度范围: -25℃~+85℃  
**Insulation resistance:**≥100MΩ  
 绝缘电阻: ≥100MΩ  
**Contact resistance:** ≤30mΩ  
 接触电阻: ≤30mΩ  
 After environment testing: ≤40mΩ  
 环境试验后: ≤40mΩ  
**Insulation O.D.:** 0.28±0.02mm(AWG#36)  
 0.32±0.02mm(AWG#34)  
**绝缘材料:** 0.28±0.02mm(AWG#36)  
 0.32±0.02mm(AWG#34)

**X0600 H I-XX X-LP HF**

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category: H-HSG
- ③ Welding Board Angle: I-HSG-hardware
- ④ Row No.-Pin No.: XX-Single row
- ⑤ Plating sytle: G-Gold plated
- ⑥ Material: LP-LCP 94V-0
- ⑦ HF-Halogen Free

Poles	Dimensions(mm)			
	A	B	C	D
2	1.36	1.80	0.60	1.65
4	2.56	3.00	1.80	2.85
5	3.16	3.60	2.40	3.45
6	3.76	4.20	3.00	4.05
8	4.96	5.40	4.20	5.25
10	6.16	6.60	5.40	6.45
12	7.36	7.80	6.60	7.65
16	9.76	10.20	9.00	10.05

X0600HI-XXG-LPHF	LCP UL94V-0 Halogen Free(Black)	AWG#36/AWG#34	0.32Max	Phosphor Bronze	Gold-Flash	X0600W
PART NO	Material	Wire Range	Insulation	Material(Terminal)	Finish(Terminal)	Suitable XKB Terminal

广东星坤科技股份有限公司

生 日期  
 日期

文件工程章

REVISIONS  
 DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.: 0.60mm IDC Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
INDUSTRIAL PRECISION CO., LIMITED			WEIGHT SHEET REVISION 1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)