



■ Specifications :

- Voltage rating: 30 V AC / DC
- Current rating: 0.5A AC / DC
- Withstanding voltage: 200V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: $\geq 100M\Omega$
- Contact resistance: $\leq 20m\Omega$
- After environmental testing: $\leq 40m\Omega$

X0800 H-XX -46 HF

- ① Series No.
- ② Category : H-HSG
- ③ Row No. Pin No. XX-02P~20P
- ④ Material: 46-PA46 94V-0
- ⑤ HF-Halogen Free

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
02	0.80	1.80	4.40	12	8.80	9.80	12.40
03	1.60	2.60	5.20	13	9.60	10.6	13.2
04	2.40	3.40	6.00	14	10.4	11.4	14.0
05	3.20	4.20	6.80	15	11.2	12.2	14.8
06	4.00	5.00	7.60	16	12.0	13.0	15.6
07	4.80	5.80	8.40	17	12.8	13.8	16.4
08	5.60	6.60	9.20	18	13.6	14.6	17.2
09	6.40	7.40	10.0	19	14.4	15.4	18.0
10	7.20	8.20	10.8	20	15.2	16.2	18.8
11	8.00	9.00	11.6				

X0800H-XX-46HF	PA46 UL 94V-0 Halogen Free	X0800T	X0800W
PART NO	Material(Wafer)	Suitable XKB Terminal	Suitable XKB Terminal

广东星坤科技股份有限公司

生效

ΔX	日期
ΔX	日期
ΔX	日期
MARK	DESCRIPTION

文件工程章

REVISIONS

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: X0800H-XX-46HF
DWN	DATE	VIEW:	PART NO.: 0.8mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)