



**Specifications:**

规格:  
**Voltage rating:**30V AC/DC  
**额定电压:** 30V AC/DC  
**Current rating:** 0.5A AC/DC  
**额定电流:** 0.5A AC/DC  
**Withstanding voltage:**200V AC/minute  
**耐压电压:** 200V AC/分钟  
**Temperature range:**-25℃~+85℃  
**温度范围:** -25℃~+85℃  
**Insulation resistance:**≥100MΩ  
**绝缘电阻:** ≥100MΩ  
**Contact resistance:** ≤20mΩ  
**接触电阻:** ≤20mΩ  
**After environment testing:** ≤40mΩ  
**环境试验后:** ≤40mΩ

**X0800 H 1 - XX X - N0 HF**

① ②③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category: H-HSG
- ③ Welding Board Angle: I-HSG+hardware
- ④ Row No.-Pin No.: XX-Single row
- ⑤ Plug the Pin & Special No. G-Gold Plating
- ⑥ Material: N0-PA66 94V-0
- ⑦ HF-Halogen free

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
2	0.80	1.78	2.40	12	8.80	9.78	10.40
3	1.60	2.58	3.20	13	9.60	10.58	11.20
4	2.40	3.38	4.00	14	10.40	11.38	12.00
5	3.20	4.18	4.80	15	11.20	12.18	12.80
6	4.00	4.98	5.60	16	12.00	12.98	13.60
7	4.80	5.78	6.40	17	12.80	13.78	14.40
8	5.60	6.58	7.20	18	13.60	14.58	15.20
9	6.40	7.38	8.00	19	14.40	15.38	16.00
10	7.20	8.18	8.80	20	15.20	16.18	16.80
11	8.00	8.98	9.60				

X0800HI-XX-N0HF	Nylon 66 UL 94V-0 Halogen Free	AWG#32-36	0.39mm[Max]	Phosphor Bronze	Gold-Flash	X0800W
PART NO	Material	Suitable X/B Terminal	Insulation O.D	Material(Terminal)	Finish(Terminal)	Suitable X/B Terminal

广东星坤科技股份有限公司

生 日期  
 日期

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGLAR	±5°			
L ≤ 4	±0.2			
4 < L ≤ 16	±0.3			
16 < L ≤ 63	±0.4			
L > 63	±0.5			

DSND	DATE	SCALE: NA	MODEL TYPE:
DWN	DATE	VIEW:	PART NO.: 0.80mm IDC Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g SHEET 1/1 REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)