

Specifications:

规格:
Voltage rating: 30V AC/DC
额定电压: 30V AC/DC
Current rating: 0.5A AC/DC
额定电流: 0.5A AC/DC
Withstanding voltage: 200V AC/minute
耐压电压: 200V AC/分钟
Temperature range: -25°C ~ +85°C
温度范围: -25°C ~ +85°C
Insulation resistance: ≥100MΩ
绝缘电阻: ≥100MΩ
Contact resistance: ≤20mΩ
接触电阻: ≤20mΩ
After environment testing: ≤40mΩ
环境试验后: ≤40mΩ

X0800 T-P XX X


① ② ③ ④

① Series Number


② Category: T-terminal

③ Material: P-Phosper bronze


⑦ SN-Bringht Ni:30-50u " SN:70-120u" V01 -All Gold Flash



SECTION-B-B



SECTION-A-A



X0800T-PSN	High conductive Brass	AWG #32-36	0.38mm (Max)	Phosphor Bronze	Tin-Plated	X0800V
X0800T-PV01						
PART NO	Material	Wire Range	Insulation O.D	Material (Terminal)	Finish (Terminal)	Suitable XKB Terminal

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS
 DATE REVISED APPROVED

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: X1259HV-XX-N0
DWN	DATE	VIEW:	PART NO.: 0.80mm IDC Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
VXP INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)