



Poles	Dimension(mm)			Poles	Dimension(mm)		
	A	B	C		A	B	C
2	0.80	1.90	3.78	12	8.80	9.90	11.78
3	1.60	2.70	4.58	13	9.60	10.70	12.58
4	2.40	3.50	5.38	14	10.40	11.50	13.38
5	3.20	4.30	6.18	15	11.20	12.30	14.18
6	4.00	5.10	6.98	16	12.00	13.10	14.98
7	4.80	5.90	7.78	17	12.80	13.90	15.78
8	5.60	6.70	8.58	18	13.60	14.70	16.58
9	6.40	7.50	9.38	19	14.40	15.50	17.38
10	7.20	8.30	10.18	20	15.20	16.30	18.18
11	8.00	9.10	10.98				

**Specifications:**

规格:  
**Voltage rating:**30V AC/DC  
 额定电压: 30V AC/DC  
**Current rating:** 0.5A AC/DC  
 额定电流: 0.5A AC/DC  
**Withstanding voltage:**200V AC/minute  
 耐压电压: 200V AC/分钟  
**Temperature range:**-25℃ ~ +85℃  
 温度范围: -25℃ ~ +85℃  
**Insulation resistance:**≥100MΩ  
 绝缘电阻: ≥100MΩ  
**Contact resistance:** ≤20mΩ  
 接触电阻: ≤20mΩ  
**After environment testing:** ≤30mΩ  
 环境试验后: ≤30mΩ

**X800 WR S - XX X- LP XX XX**  
 ① ②③④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Category: W-wafer
- ③ Welding Board Angle: R-90°
- ④ Welding Way: S-SMT
- ⑤ Row No. Pin No. XX-Single
- ⑥ Plug the Pin & Special NO.:HF-Halogen free
- ⑦ Material: LP-LCP 94V-0
- ⑧ Planting Category : V01:All Gold-Flash;  
SN-Bright tin plating
- ⑨ Color: Blank-natural color; BK-black

PART NO	Material	Material(Pin)	Finishing	Material (Solder Tabs)	Finish (Solder Tabs)	Suitable XQB Termination
X800WRS-XXHF-LP-V01BK	PART UL 94V-0 Black (Halogen-free)		Gold-Flash		Gold-Flash	
X800WRS-XXHF-LP-SNBK	PART UL 94V-0 (Halogen-free)	Phosphor Bronze	Gold-Flash	Brass	Gold-Flash	0800H
X800WRS-XXHF-LP-SN			Gold-Flash		Gold-Flash	
X800WRS-XXHF-LP-V01	LCP UL 94V-0 Halogen-free		Tin-Plated		Tin-Plated	

广东星坤科技股份有限公司  
 生 日期  
 文件工程章  
 REVISIONS  
 www.xkpcb.com www.helixkb.com www.helixkb.cn

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.: 0.80mm IDC Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
UNSPECIFIED TOLERANCES			WEIGHT
VXD INDUSTRIAL PRECISION CO., LIMITED			SHEET
			REVISION
			1.0g
			1/1
			A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)