



Specifications:

规格:  
 Voltage rating 30V AC/DC  
 额定电压: 30V AC/DC  
 Current rating: 0.5A AC/DC  
 额定电流: 0.5A AC/DC  
 Withstanding voltage 200V AC/minute  
 耐压电压: 200V AC/分钟  
 Temperature range -25℃~+85℃  
 温度范围: -25℃~+85℃  
 Insulation resistance ≥100MΩ  
 绝缘电阻: ≥100MΩ  
 Contact resistance: ≤20mΩ  
 接触电阻: ≤20mΩ  
 After environment testing: ≤40mΩ  
 环境试验后: ≤40mΩ

X800 W V S - XX X LP XX XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① Series No.

② Category: W-Water

③ Welding Board Angle: V-180°

④ Welding Way: S-SMT

⑤ Row No.-Pin No. XX-Single row

⑥ Plug the Pin & Special NO. HF-Halogen free

⑦ Material: LP-LCP 94V-0

⑧ Plating Category: V01 All Gold-Flash; SN-5 Bright tin plating

⑨ Color: Blank-natural color, BK-black

Poles	Dimension(mm)			Poles	Dimension(mm)		
	A	B	C		A	B	C
2	0.80	1.90	3.78	12	8.80	9.90	11.78
3	1.80	2.70	4.58	13	9.60	10.70	12.58
4	2.40	3.50	5.38	14	10.40	11.50	13.38
5	3.20	4.30	6.18	15	11.20	12.30	14.18
6	4.00	5.10	6.98	16	12.00	13.10	14.98
7	4.80	5.90	7.78	17	12.80	13.90	15.78
8	5.60	6.70	8.58	18	13.60	14.70	16.58
9	6.40	7.50	9.38	19	14.40	15.50	17.38
10	7.20	8.30	10.18	20	15.20	16.30	18.18
11	8.00	9.10	10.98				

PART NO	Material	Material(Pin)	Finish(pin)	Material (Solder Tabs)		Finish (Solder Tabs)	Substrate / PCB Terminal
				Gold-Flash	Brass		
X800WRS-KXH- LP-V01BK	PART UL 94V-0 Black (Halogen-free)	Phosphor Bronze	Gold-Flash	Gold-Flash			090H
X800WRS-KXH- LP-SNBK	PART UL 94V-0 (Halogen-free)	Phosphor Bronze	Gold-Flash	Gold-Flash			090H
X800WRS-KXH- LP-SN	LCP UL 94V-0 Halogen-free	Phosphor Bronze	Gold-Flash	Gold-Flash			090H
X800WRS-KXH- LP-V01	LCP UL 94V-0 Halogen-free	Phosphor Bronze	Tin-Plated	Tin-Plated			090H

广东星坤科技股份有限公司

生 日期

Δ% 文件工程章

REVISIONS

www.xkpcb.com www.hellixkb.com

UNSPECIFIED TOLERANCES

www.okeyac.com

DSND	DATE	SCALE: NA	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
VPP			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)