



■ Specifications :

- Voltage rating: 50 V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤20mΩ
- Material: Phosphor Broze
- Finish:Plated Tin over Nickel
- Applicable wires :AWG#28-#32
- Insulation O.D.0.4 to 0.8mm

X1011 T-P XX

① ② ③ ④

- ① SeriesNumber
- ② Category : T-terminal
- ③ Material:P-Phosphor bronze
- ④ Plating style:
V01-ALL Gold Flash;SN-Bright tin plating

X1011T-PV01	Phosphor Bronze	AWG#28-32	0.8mm(Max)	Stamping Before Pating;30u" Ni;Whole Gold;Gold Flash	X1011H
X1011T-PSN	Phosphor Bronze	AWG#28-32	0.8mm(Max)	Stamping Before Plating :30u" Ni;70u" Sn	
PARY NO	Matrial	Wire Range	Insulation O.D.	Finish	Suitable XKB Terminal

广东星坤科技股份有限公司

生 效 日期

文件工程章

REVISIONS	DATE	REVISED	APPROVED	DESCRIPTION

DSND	DATE	SCALE: N/A	MODEL TYPE: X1011T-PSN
DWN	DATE	VIEW:	PART NO.: 1.0mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)