



**Specifications:**

规格:  
**Voltage rating:** 50V AC/DC  
**额定电压:** 50V AC/DC  
**Current rating:** 1A AC/DC  
**额定电流:** 1A AC/DC  
**Withstanding voltage:** 250V AC/minute  
**耐压电压:** 250V AC/分钟  
**Temperature range:** -40°C ~ +85°C  
**温度范围:** -40°C ~ +85°C  
**Insulation resistance:** ≥100MΩ  
**绝缘电阻:** ≥100MΩ  
**Contact resistance:** ≤20mΩ  
**接触电阻:** ≤20mΩ  
**After environment testing:** ≤40mΩ  
**环境试验后:** ≤40mΩ

**X1102 H X - 2xXX X-46 XX**

① ②③ ④ ⑤⑥ ⑦

- ① Series No.
- ② Category: H-HSG
- ③ Welding Board Angle: Blank-ordinary
- ④ Row No.-Pin No.: 2xXX-Double row
- ⑤ Plug the Pin & special No.
- ⑥ Material: 46-PA46 94V-0
- ⑦ Color: Blank-natural color  
BK-Black

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
2x03	2.00	6.60	4.00	2x13	12.00	16.60	14.00
2x04	3.00	7.60	5.00	2x14	13.00	17.60	15.00
2x05	4.00	8.60	6.00	2x15	14.00	18.60	16.00
2x06	5.00	9.60	7.00	2x16	15.00	19.60	17.00
2x07	6.00	10.60	8.00	2x17	16.00	20.60	18.00
2x08	7.00	11.60	9.00	2x18	17.00	21.60	19.00
2x09	8.00	12.60	10.00	2x19	18.00	22.60	20.00
2x10	9.00	13.60	11.00				
2x11	10.00	14.60	12.00				
2x12	11.00	15.60	13.00				

X1102H-2xxx-46BK	Nylon 46 UL 94V-0 Black	X1102T	X1102W
X1102H-2xxx-46	Nylon 46 UL 94V-0		
PART NO	Material	Suitable X KB Terminal	Suitable X KB Terminal

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.xkpcb.com www.hellixkb.cn

ANGLAR	±5°	DSND		DATE		SCALE: N/A	MODEL TYPE:
L ≤ 4	±0.2	DWVN		DATE		VIEW:	PART NO.:
4 < L ≤ 16	±0.3	CHKD		DATE		UNIT: mm/in	1.00mm Crimp Style Connectors
16 < L ≤ 63	±0.4	APPD		DATE		SIZE: A4	DWG NO.:
L > 63	±0.5	VVP		DATE			X1102H-2xXX-46
							WEIGHT
							1.0g
							SHEET
							1/1
							REVISION
							A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)