



■ Specifications :

- Voltage rating: 200V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤40mΩ
- After environmental testing : ≤80mΩ

X1255 H-XX A-N0 XX
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Category : H-HSG
- ③ Row No.-Pin No.: XX-04P~06P
- ④ Plug the Pin & Special N0:A-Double Salient
- ⑤ Material : N0-PA66 94V-0
- ⑥ Whether containing halogen:HF-Halogen free

Poles	Dimension □ mm □		
	A	B	C
04	3.75	8.60	6.40
05	5.00	9.85	7.65
06	6.25	11.10	8.90
07	7.50	12.35	10.15

X1255H-XXA-N0HF	PA66 UL 94V-0 Halogen Free	X1255T	X1255W
X1255H-XXA-N0	PA66 UL 94V-0		
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: X1255H-XXA-N0XX		
ΔX					ANGLAR ±5°	DWN	DATE	VIEW:	PART NO.: 1.25mm Crimp Style Connectors		
ΔX					L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm/in			
ΔX					4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	DWG NO.:		
					16 < L ≤ 63 ±0.4						
					L > 63 ±0.5						
REVISIONS						XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn									1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)