




SECTION: A-A
SCALE: 1:1



SECTION: B-B
SCALE: 1:1



SECTION: C-C
SCALE: 1:1



Specifications:

规格:
Voltage rating: 50V AC/DC
额定电压: 50V AC/DC
Current rating: 1A AC/DC
额定电流: 1A AC/DC
Withstanding voltage: 250V AC/minute
耐压电压: 250V AC/minute
Temperature range: -25°C ~ +85°C
温度范围: -25°C ~ +85°C
Insulation resistance: ≥100MΩ
绝缘电阻: ≥100MΩ
Contact resistance: ≤20mΩ
接触电阻: ≤20mΩ
After environmental testing: ≤20mΩ
环境测试后: ≤20mΩ

X1259 T X- P SN X-X

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series Number
- ② Category: T-terminal
- ③ Shape: Blank-ordinary
- ④ Material: P-Phosphor bronze
- ⑤ Planting style: SN-Bright tin plating
- ⑥ Planting method: Blank-Stamping before plating
- ⑦ Mold No./Mark/Special No.

X1259T-PSN	Phosphor Bronze	AWG#28-32	1.00MM(MAX)	Stamping Before Plating: 30u"MIN.Ni;70u"Sn	1259H
PART NO	Material	Material(Pin)	Finish(Pin)	Finish	Used In XKB Housing

广东星坤科技股份有限公司

生	日期
发	
Δ	
文件工程章	

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE:
				ANGLAR ±5°	DWN	DATE	VIEW: ④	PART NO.:
				L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm/in	1.25 mm Crimp Style Connectors
				4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	DWG NO.:
				16 < L ≤ 63 ±0.4				X1259T-PSN
				L > 63 ±0.5	VXP INDUSTRIAL PRECISION CO., LIMITED			WEIGHT
								1.0g
								SHEET
								1/1
								REVISION
								A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)