



Recommended P.C.B. Layout
General Tolerance±0.05

Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 1A AC / DC
- Withstanding voltage: 500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥100MΩ
- Contact resistance: ≤30mΩ
- After environmental testing : ≤40mΩ

X1276 KV X-2*XX B-XX XX XX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Category : K-Cowfish Longhorn Connector
- ③ Welding Board Angle: V- Straight 180°
- ④ Welding Way: Blank-DIP
- ⑤ Row No.-Pin No.: 2*XX-Double Row
- ⑥ Plug the Pin & Special No.: B-With Convex platform
- ⑦ Material : 6T-PA6T 94V-0
- ⑧ Planting Category: V01-All Gold Flash;
SN-Bright tin plating ;
- ⑨ Color : Blank-natural color

X1276KV-2*XXB-6T5N	PA6T UL 94V-0	Brass	Tin-plated	X1276Hl
X1276KV-2*XXB-6TV01			Gold-Flash	
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With XKB Housing

广东星坤科技股份有限公司

生	日期
發	日期
ΔX	
MARK	
文件工程章	

DESCRIPTION	DATE	REVISED	APPROVED	ANGULAR	±5°
				L ≤ 4	±0.2
				4 < L ≤ 16	±0.3
				16 < L ≤ 63	±0.4
				L > 63	±0.5
REVISIONS				UNSPECIFIED TOLERANCES	
www.xk-ug.cn www.hellokxb.com www.hellokxb.cn					

DSND	DATE	SCALE: N/A
DWN	DATE	VIEW:
CHKD	DATE	UNIT: mm/in
APPD	DATE	SIZE: A4
KKB INDUSTRIAL PRECISION CO., LIMITED		

MODEL TYPE:	X1276KV-2*XXB-6TXXX	
PART NO.:	1.27mm Crimp Style Connector	
DWG NO.:		
WEIGHT	SHEET	REVISION
1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)