



PCB LAYOUT

XKB Connectivity

XKB Connectivity

■ 规格 Specifications:

- 额定电压 Voltage rating: 250VAC/DC。
- 额定电流 Current rating: 1A AC/DC
- 耐电压 Withstanding voltage: 300V AC/minute
- 温度区间 Temperature range: -40°C to +105°C
- 绝缘电阻 Insulation resistance: ≥500MΩ Min
- 接触电阻 Contact resistance: ≤20MΩ Max
- 材料 Material: PA6T 94V-0
- 镀层 Plating Category: 1U"Gold
- 波峰焊温度 Wave soldering temperature: 255±5°C, 10s

XKB Connectivity

X1311WR-XXJ-C26D40

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category: W-Wafer
- ③ Welding Board Angle: R-Stright 90°
- ④ Row No -Pin No: XX-01P-40P
- ⑤ Plastic height: J=1.0mm
- ⑥ Plastic length: C=2.6mm
- ⑦ Plastic length: C=4.0mm

XKB Connectivity

| | | | | |
|--------------------|------------|---------------|-------------|-----------------------|
| X1311WR-XXJ-C26D40 | PA6T 94V-0 | Brass | 1U"Gold | X1311F |
| PART NO | Material | Material(Pin) | Finish(Pin) | Suitable XKB Terminal |

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

| | | | |
|-----------------------------------|------|-------------|--|
| DSND | DATE | SCALE: N/A | MODEL TYPE: X1311WR-XXJ-C26D40 |
| DWNN | DATE | VIEW: ① | PART NO.: 1.27mm Crimp Style Connector |
| CHKD | DATE | UNIT: mm/in | DWG NO.: |
| APPD | DATE | SIZE: A4 | |
| INDUSTRIAL PRECISION CO., LIMITED | | | WEIGHT 1.0g SHEET 1/1 REVISION A0 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)