



Specifications:

规格:
Voltage rating:150V AC/DC
 额定电压: 150V AC/DC
Current rating:3A AC/DC
 额定电流: 3A AC/DC
Withstanding voltage:500V AC/minute
 耐受电压: 500V AC/分钟
Temperature range:-25°C~+85°C
 温度范围: -25°C~+85°C
Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
Contact resistance:≤20mΩ
 接触电阻: ≤20mΩ
After environmental testing:≤40mΩ
 环境测试后: ≤40兆欧

X1503 H-XX-N0

① ② ③ ④

1. Series No.
2. Category: H-HSG
3. Row No-Pin No: XX-04P~12P
4. Material: N0-PA66 94V-0

Poles	Dimensions(mm)			
	A	B	C	D
02		6.95	5.95	5.55
03	3.00	8.45	7.45	7.05
04	4.50	9.95	8.95	8.55
05	6.00	11.45	10.45	10.05
06	7.50	12.95	11.95	11.55
07	9.00	14.45	13.45	13.05
08	10.50	15.95	14.95	14.55
09	12.00	17.45	16.45	16.05
10	13.50	18.95	17.95	17.55
11	15.00	20.45	19.45	19.05
12	16.50	21.95	20.95	20.55

X1503H-XX-N0	PA66 UL 94V-0	X1503T	X1503W
PART NO	Material	Suitable Terminal	Suitable XKB

广东星坤科技股份有限公司

生	日期									units: mm
ΔX										tolerance:
ΔX										X.X ±0.2mm
ΔX										X.XX ±0.1mm
MARK										X.XXX ±0.05mm
文件工程章										UNSPECIFIED TOLERANCES
REVISIONS										
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn										

DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm/in	1.50mm Crimp Style Connectors	
APPD		DATE		SIZE: A4	DWG NO.: X1503H-XX-N0	
KKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET	REVISION
				1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)