

Specifications:

规格:


Voltage rating: 150V AC/DC
 额定电压: 150V AC/DC
 Current rating: 3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage: 500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range: -25°C ~ +85°C
 温度范围: -25°C ~ +85°C
 Insulation resistance: ≥1000MΩ
 绝缘电阻: ≥1000MΩ

Contact resistance: ≤20mΩ
 接触电阻: ≤20mΩ
 After environmental testing: ≤40mΩ
 环境测试后: ≤40mΩ
 Wire Range: #24-28
 电线范围: #24-28
 Insulation OD: 1.10mm (Max)
 绝缘外径: 1.10mm (最大值)


X1503 T- P XX

- ① ② ③ ④


1. Series Number
2. Category: T-terminal
3. Material: P-Phosphor bronze
4. Plating Code: V01-Gold Flash
SN-Bright tin plating



SECTION: A-A
SCALE: 1:1



SECTION: B-B
SCALE: 1:1



X1503T-PV01	Phosphor Bronze	AWG#24-28	1.10mm(Max)	Stamping Before Plating: 30u"Ni MIN, Gold Flash	X1503H
X1503T-PSN				Stamping Before Plating: 30u"Ni MIN, 70u"Sn Min	
PART NO	Material	Wire Range	Insulation OD	Finish	Suitable: XKB

广东星坤科技股份有限公司

生	日期
效	日期
效	日期
效	日期
MARK	文件工程章

units:	mm
tolerance:	
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm
	UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm/in	1.50mm Crimp Style Connectors	
APPD		DATE		SIZE: A4	DWG NO.: X1503T-PXXX	
KKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET	REVISION
				1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)