



Specifications:

规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating:3A AC/DC  
 额定电流: 3A AC/DC  
 Withstanding voltage:800V AC/minute  
 耐受电压: 800V AC/分钟  
 Temperature range:-25℃-+85℃  
 温度范围: -25℃-+85℃  
 Insulation resistance:≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:≤10mΩ  
 接触电阻: ≤10mΩ  
 After environmental testing:≤20mΩ  
 环境测试后: ≤20兆欧

X2015H-2xXX-N0

① ② ③ ④

- 1.Series No.
- 2.Category:H-HSG
- 3.Row No-Pin No: XX-02P~15P
- 4.Material: N0-PA66 94V-0

Poles	Dimensions(mm)		Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B		A	B
2x02	2.00	5.90	2x09	16.00	19.90	2x16	30.00	33.90
2x03	4.00	7.90	2x10	18.00	21.90	2x17	32.00	35.90
2x04	6.00	9.90	2x11	20.00	23.90	2x18	34.00	37.90
2x05	8.00	11.90	2x12	22.00	25.90	2x19	36.00	39.90
2x06	10.00	13.90	2x13	24.00	27.90	2x20	38.00	41.90
2x07	12.00	15.90	2x14	26.00	29.90			
2x08	14.00	17.90	2x15	28.00	31.90			

X2015H-2xXX-N0	Nylon 66 UL 94V-0	X2015T	X2015W
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

广东星坤科技股份有限公司

生	日期
效	
效	
效	
MARK	文件工程章

DESCRIPTION	DATE	REVISED	APPROVED	units: mm
				tolerance:
				X.X ±0.2mm
				X.XX ±0.1mm
				X.XXX ±0.05mm
				UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector	
DWN		DATE		VIEW:	PART NO.: 2.00mm Crimp Style Connectors	
CHKD		DATE		UNIT: mm/in	DWG NO.: X2015H-2xXX-N0	
APPD		DATE		SIZE: A4		
KKB INDUSTRIAL PRECISION CO., LIMITED				WEIGHT	SHEET	REVISION
				1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)