



PCB LAYOUT

Specifications:

规格:
 Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
 Current rating:3A AC/DC
 额定电流: 3A AC/DC
 Withstanding voltage:800V AC/minute
 耐受电压: 800V AC/分钟
 Temperature range:-25℃~+85℃
 温度范围: -25℃~+85℃
 Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
 Contact resistance:≤10mΩ
 接触电阻: ≤10mΩ
 After environmental testing:≤20mΩ
 环境测试后: ≤20兆欧

X2015 W V-2xXX-N0SN

① ② ③ ④ ⑤ ⑥

- 1.Series No.
- 2.Category:W-WAFER
- 3.Welding Board Angle:V-Straight 180°
- 4.Row No-Pin N0:2xXX-2x02P~2x20P
- 5.Material: N0-PA66 94V-0
- 6.Plating Category: SN-Bright Tin plating

Poles	Dimensions(mm)		Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B		A	B
2x02	2.00	6.00	2x09	16.00	20.00	2x16	30.00	34.00
2x03	4.00	8.00	2x10	18.00	22.00	2x17	32.00	36.00
2x04	6.00	10.00	2x11	20.00	24.00	2x18	34.00	38.00
2x05	8.00	12.00	2x12	22.00	26.00	2x19	36.00	40.00
2x06	10.00	14.00	2x13	24.00	28.00	2x20	38.00	42.00
2x07	12.00	16.00	2x14	26.00	30.00			
2x08	14.00	18.00	2x15	28.00	32.00			

X2015WV-2xXX-N0SN	PA66 UL 94V-0	Brass	Tin-Plated	X2015H
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司

生	日期
效	
ΔX	
ΔX	
MARK	文件工程章
DESCRIPTION	REVISIONS

units:	mm
tolerance:	
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm
UNSPECIFIED TOLERANCES	

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	Wire to board connector
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	2.00mm Crimp Style Connectors
			DWG NO.:
			X2015WV-2xXX-N0SN
YKB INDUSTRIAL DECISION CO. LIMITED			WEIGHT SHEET REVISION

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)