


PCB LAYOUT(Tolerance:±0.05)



Specifications:

规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating:3A AC/DC  
 额定电流: 3A AC/DC  
 Withstanding voltage:1000V AC/minute  
 耐受电压: 1000V AC/分钟  
 Temperature range:-25°C~+85°C  
 温度范围: -25°C~+85°C  
 Insulation resistance:≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:≤30mΩ  
 接触电阻: ≤30mΩ  
 After environmental testing:≤50mΩ  
 环境测试后: ≤50兆欧

X2026 W R S-2xXXD- LPSW

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- 1.Series No
- 2.Category:W-WAFER
- 3.Welding Board Angle:R-Right Angle 90°
- 4.Welding Way:S-SMT
- 5.Row No-Pin No:2xXX-2x02P~2x16P
- 6.Plug the Pin&Special NO:  
D-With Lock in the middle
- 7.Material:LP-LCP 94V-0
- 8.Plating Category:SW-Fog Tin Plating

| poles | Dimensions(mm) |       |       |       | poles | Dimensions(mm) |       |       |       |
|-------|----------------|-------|-------|-------|-------|----------------|-------|-------|-------|
|       | A              | B     | C     | D     |       | A              | B     | C     | D     |
| 2x02  | 2.00           | 5.00  | 9.00  | 3.00  | 2x10  | 18.00          | 21.00 | 25.00 | 15.00 |
| 2x03  | 4.00           | 7.00  | 11.00 | 3.00  | 2x11  | 20.00          | 23.00 | 27.00 | 17.00 |
| 2x04  | 6.00           | 9.00  | 13.00 | 3.00  | 2x12  | 22.00          | 25.00 | 29.00 | 19.00 |
| 2x05  | 8.00           | 11.00 | 15.00 | 5.00  | 2x13  | 24.00          | 27.00 | 31.00 | 21.00 |
| 2x06  | 10.00          | 13.00 | 17.00 | 7.00  | 2x14  | 26.00          | 29.00 | 33.00 | 23.00 |
| 2x07  | 12.00          | 15.00 | 19.00 | 9.00  | 2x15  | 28.00          | 31.00 | 35.00 | 25.00 |
| 2x08  | 14.00          | 17.00 | 21.00 | 11.00 | 2x16  | 30.00          | 33.00 | 37.00 | 27.00 |
| 2x09  | 16.00          | 19.00 | 23.00 | 13.00 |       |                |       |       |       |

|                     |              |               |             |                       |
|---------------------|--------------|---------------|-------------|-----------------------|
| X2026WRS-2xXXD-LPSW | LCP UL 94-V0 | Brass         | Tin-Plated  | X2026H-D              |
| PART NO             | Material     | Material(pin) | Finish(Pin) | Suitable XKB Terminal |

广东星坤科技股份有限公司

|      |       |
|------|-------|
| 生    | 日期    |
| 效    |       |
| 效    |       |
| 效    |       |
| MARK | 文件工程章 |

|                        |         |
|------------------------|---------|
| units:                 | mm      |
| tolerance:             |         |
| X.X                    | ±0.2mm  |
| X.XX                   | ±0.1mm  |
| X.XXX                  | ±0.05mm |
| UNSPECIFIED TOLERANCES |         |

|                                       |      |             |  |
|---------------------------------------|------|-------------|--|
| DSND                                  | DATE | SCALE: N/A  | MODEL TYPE:<br>Wire to board connector |
| DWN                                   | DATE | VIEW:       | PART NO.:                              |
| CHKD                                  | DATE | UNIT: mm/in | 2.00mm Crimp Style Connectors          |
| APPD                                  | DATE | SIZE: A4    | DWG NO.:                               |
| XKB INDUSTRIAL PRECISION CO., LIMITED |      |             | WEIGHT<br>1.0g                         |
|                                       |      |             | SHEET<br>1/1                           |
|                                       |      |             | REVISION<br>A0                         |

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)