



Specifications:

规格:
Voltage rating:250V AC/DC
 额定电压: 250V AC/DC
Current rating:3A AC/DC
 额定电流: 3A AC/DC
Withstanding voltage:1000V AC/minute
 耐受电压: 1000V AC/分钟
Temperature range:-25°C~+85°C
 温度范围: -25°C~+85°C
Insulation resistance:≥1000MΩ
 绝缘电阻: ≥1000MΩ
Contact resistance:≤30mΩ
 接触电阻: ≤30mΩ
After environmental testing:≤50mΩ
 环境测试后: ≤50兆欧

X2026 W V X-2xXXD-XX XX XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- 1.Series No
- 2.Category:W-WAFER
- 3.Welding Board Angle:V-Straight 180°
- 4.Welding Way:Blank-DIP
- 5.Row No-Pin No:2xXX-2x02P~2x22P
- 6.Plug the Pin&Special NO:
D-With Lock in the middle
- 7.Material:46-PA46 94V-0.9T-PA9T 94V-0
4T-PA4T 94V-0
- 8.Plating Category:SN-Bright Tin Plating
V03-All Gold-Plated 3u"
- 9.Color:Blank-Natural Color

| poles | Dimensions(mm) | | | poles | Dimensions(mm) | | | Poles | Dimensions(mm) | | |
|-------|----------------|-------|-------|-------|----------------|-------|-------|-------|----------------|-------|-------|
| | A | B | C | | A | B | C | | A | B | C |
| 2x02 | 2.00 | 6.00 | 4.90 | 2x10 | 18.00 | 22.00 | 20.90 | 2x18 | 34.00 | 38.00 | 36.90 |
| 2x03 | 4.00 | 8.00 | 6.90 | 2x11 | 20.00 | 24.00 | 22.90 | 2x19 | 36.00 | 40.00 | 38.90 |
| 2x04 | 6.00 | 10.00 | 8.90 | 2x12 | 22.00 | 26.00 | 24.90 | 2x20 | 38.00 | 42.00 | 40.90 |
| 2x05 | 8.00 | 12.00 | 10.90 | 2x13 | 24.00 | 28.00 | 26.90 | 2x30 | 58.00 | 62.00 | 60.90 |
| 2x06 | 10.00 | 14.00 | 12.90 | 2x14 | 26.00 | 30.00 | 28.90 | | | | |
| 2x07 | 12.00 | 16.00 | 14.90 | 2x15 | 28.00 | 32.00 | 30.90 | | | | |
| 2x08 | 14.00 | 18.00 | 16.90 | 2x16 | 30.00 | 34.00 | 32.90 | | | | |
| 2x09 | 16.00 | 20.00 | 18.90 | 2x17 | 32.00 | 36.00 | 34.90 | | | | |

| | | | | |
|-------------------------|------------|---------------|-----------------|-----------------------|
| X2026WV-2xXXD-4T SN | PA4T 94V-0 | Brass | Tin-Plated | X2026H-D |
| X2026WV-2xXXD-9T V03 | PA9T 94V-0 | | Gold-Plated 3u" | |
| X2026WV-2xXXD-46 SN | PA46 94V-0 | | Tin-Plated | |
| PART NO | Material | Material(pin) | Finish(Pin) | Suitable XKB Terminal |

广东星坤科技股份有限公司
 Conn.line
 1.0mm/1.0mm/0.5mm/0.5mm/0.5mm
 General Tolerance:±0.03

| | | | | | | |
|-------|-----------|------|---------|----------|--|------------------------|
| 生 | 日期 | | | | | units: mm |
| 效 | | | | | | tolerance: |
| ΔX | | | | | | X.X ±0.2mm |
| ΔX | | | | | | X.XX ±0.1mm |
| MARK | | | | | | X.XXX ±0.05mm |
| 文件工程章 | REVISIONS | DATE | REVISED | APPROVED | | UNSPECIFIED TOLERANCES |
| | | | | | | |

| | | | | | | |
|---------------------------------------|--|------|--|-------------|--|----------|
| DSND | | DATE | | SCALE: N/A | MODEL TYPE: Wire to board connector | |
| DWN | | DATE | | VIEW: | PART NO.: 2.00mm Crimp Style Connectors | |
| CHKD | | DATE | | UNIT: mm/in | DWG NO.: X2026WV-2xXXD-XXXXX | |
| APPD | | DATE | | SIZE: A4 | | |
| KKB INDUSTRIAL PRECISION CO., LIMITED | | | | WEIGHT | SHEET | REVISION |
| | | | | 1.0g | 1/1 | A0 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)