



Specifications:  
 规格:  
 Voltage rating:250V AC/DC  
 额定电压: 250V AC/DC  
 Current rating: 3A AC / DC  
 额定电流: 3A AC / DC  
 Withstanding voltage: 1000V AC/minute  
 耐压电压: 1000V AC/minute  
 Temperature range:-25℃~+85℃  
 温度范围: -25℃~+85℃  
 Insulation resistance:≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
 Contact resistance: ≤10mΩ  
 接触电阻: ≤10mΩ  
 After environmental testing:≤20mΩ  
 环境测试后: ≤20mΩ

X2508 W V S- XX X - 9T XX XX

- ① Series No.
- ② Category: W-WAFER
- ③ Welding Board Angle: V-Stringht 180°
- ④ Welding Way:
- ⑤ Row No.-Pin No. XX-02P~15P
- ⑥ Plug the Pin & Special No.
- ⑦ Material: 9T-PA9T 94V-0
- ⑧ Plating Category SW-Fog Tin plating
- ⑨ Color: Blank-Natural Color

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
2	2.50	10.00	5.30	10	22.50	30.00	6.40
3	5.00	12.50		11	25.00	32.50	
4	7.50	15.00		12	27.50	35.00	
5	10.00	17.50	6.40	13	30.00	37.50	
6	12.50	20.00		14	32.50	40.00	
7	15.00	22.50		15	35.00	42.50	
8	17.50	25.00					
9	20.00	27.50					

X2508WVS-XX-9TSW	PA9T UL 94V-0	Brass	Tin-Plated	Brass	Tin Plating	X2508H
PART NO	Material	Material(Pin)	Finish(Pin)	Material (Solder Tabs)	Finish (Solder Tabs)	Mates With Housing

广东星坤科技股份有限公司  
 RECOMMENDED PCB LAYOUT

生	日期
發	
Δ	
文件工程	章

UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: NA	MODEL TYPE:
ANGULAR ±5°	DWN	DATE	VIEW:	PART NO.:
L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm/in	2.50 mm Crimp Style Connectors
4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	DWG NO.:
16 < L ≤ 63 ±0.4				X2508WVS-XX-9TSW
L > 63 ±0.5				WEIGHT
				1.0g
				SHEET
				1/1
				REVISION
				A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)