



PCB  
PCBLAYOUT

Specifications:

规格:  
Voltage rating:250V AC/DC  
额定电压: 250V AC/DC  
Current rating: 3A AC / DC  
额定电流: 3A AC / DC  
Withstanding voltage: 1000V AC/minute  
耐压电压: 1000V AC/minute  
Temperature range:-25℃~+85℃  
温度范围: -25℃~+85℃  
Insulation resistance≥1000MΩ  
绝缘电阻: ≥1000MΩ  
Contact resistance: ≤10mΩ  
接触电阻: ≤10mΩ  
After environment testing: ≤20mΩ  
环境试验后: ≤20mΩ

X2510WR-XX-N0SN

① ②③ ④ ⑤ ⑥

① Series No.

② Category: W-WAFER

③ Welding Board Angle: R-90°

④ Row No.-Pin No. XX-Single Row

⑤ Material: NO-PA66 94V-0

⑥ Planting Category SN-Bright Tin Plating

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
2	2.54	5.08	10	22.86	25.4
3	5.08	7.62	11	25.4	27.94
4	7.62	10.16	12	27.94	30.48
5	10.16	12.70	13	30.48	33.02
6	12.70	15.24	14	33.02	35.56
7	15.24	17.78	15	35.56	38.10
8	17.78	20.32			
9	20.32	22.86			

X2510WR-XX-N0SN	Nylon 66 UL 94V-0	Brass	Tin-Plated	X2510H
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With XKB Housing

广东星坤科技股份有限公司

生  
發

日  
期

文件工程章

REVISIONS

www.xkpcb.cn www.hellixkb.com www.hellixkb.com

ANGULAR ±5°  
L ≤ 4 ±0.2  
4 < L ≤ 16 ±0.3  
16 < L ≤ 63 ±0.4  
L > 63 ±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/mn	2.54 mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
XVP INDUSTRIAL PRECISION CO., LIMITED			X2510WR-XX-N0SN
			WEIGHT SHEET REVISION
			1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)