



PCB LAYOUT

A=2.5x(No of circuit-1)
B=A+5.0

Specifications:

规格:
Voltage rating: 3A 250V AC/DC
额定电压: 3A 250V AC/DC
Temperature range: -40°C ~ +105°C
温度范围: -40°C ~ +105°C
Insulator: PA66 UL 94V-0 Nature
绝缘材料: PA66 UL 94V-0 Nature
Terminal: Phosphor Bronze
端子: Phosphor Bronze

X2514 H I-XX L-X-XX

① ② ③ ④ ⑤ ⑥ ⑦

① Series No.

② Category: I-HSG

③ Welding Board Angle: I-HSG+hardware

④ Row No.-Pin No.: XX-Single row

⑤ L: With Lock

⑥ 0= Tin plated 120~200u" over Ni 30u" overall, for AWG#22-#24
1= Tin plated 120~200u" over Ni 30u" overall, for AWG#26.

G= Gold Flash over Ni 80~150u" overall.

⑦ See the Table of next page

PART NO	Material	Wire Range	Material (Terminal)	Suitable XKB Terminal
X2514HI-XXL-X-XX	PA66 94V-0	AWG #22-#24 AWG #26	Phosphor Bronze	X2514W

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.xkpcb.com www.hellixkb.com

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	X2514HI-XXL-X-XX
VVP			WEIGHT SHEET REVISION
			1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)