



**Specifications:**

规格:  
**Voltage rating:**250V AC/DC  
 额定电压: 250V AC/DC  
**Current rating:**3A AC/DC  
 额定电流: 3A AC/DC  
**Withstanding voltage:**800V AC/minute  
 耐受电压:800V AC/分钟  
**Temperature range:**-25°C~+85°C  
 温度范围: -25°C~+85°C  
**Insulation resistance:**≥1000MΩ  
 绝缘电阻: ≥1000MΩ  
**Contact resistance:**≤10mΩ  
 接触电阻: ≤10mΩ  
**After environmental testing:**≤20mΩ  
 环境测试后: ≤20兆欧

**X2530 H X-2xXX X-PT XX**

① ②③ ④ ⑤⑥ ⑦

1. Series No
2. Category:H-HSG
3. Welding Board Angle:Blank-ordinary
4. Row No-Pin No:2xXX-2x02P~2x32P
5. Plug the Pin&Special No:
6. Material:PT-PBT 94V-0
7. Color:Blank-natural color black

poles	Dimensions(mm)			poles	Dimensions(mm)			poles	Dimensions(mm)		
	A	B	C		A	B	C		A	B	C
2x02	2.54	5.52	7.12	2x13	30.48	33.46	35.06	2x24	58.42	61.40	63.00
2x03	5.08	8.06	9.66	2x14	33.02	36.00	37.60	2x25	60.96	63.94	65.54
2x04	7.62	10.60	12.20	2x15	35.56	38.54	40.14	2x26	63.50	66.48	68.08
2x05	10.16	13.14	14.74	2x16	38.10	41.08	42.68	2x27	66.04	69.02	70.62
2x06	12.70	15.68	17.28	2x17	40.64	43.62	45.22	2x28	68.58	71.56	73.16
2x07	15.24	18.22	19.82	2x18	43.18	46.16	47.76	2x29	71.12	74.10	75.70
2x08	17.78	20.76	22.36	2x19	45.72	48.70	50.30	2x30	73.66	76.64	78.24
2x09	20.32	23.30	24.90	2x20	48.26	51.24	52.84	2x31	76.20	79.18	80.78
2x10	22.86	25.84	27.44	2x21	50.80	53.78	55.38	2x32	78.74	81.72	83.32
2x11	25.40	28.38	29.98	2x22	53.34	56.32	57.92				
2x12	27.94	30.92	32.52	2x23	55.88	58.86	60.46				

X2530H-2xXX-PT	PBT UL 94V-0	X2530T	X2530W
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

广东星坤科技股份有限公司

生	日期						units: mm
ΔX							tolerance:
ΔX							X.X ±0.2mm
ΔX							X.XX ±0.1mm
MARK							X.XXX ±0.05mm
UNSPECIFIED TOLERANCES							

DSND		DATE		SCALE: N/A	MODEL TYPE: Wire to board connector
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	2.54mm Crimp Style Connectors
APPD		DATE		SIZE: A4	DWG NO.:
XKB INDUSTRIAL PRECISION CO., LIMITED					X2530H-2xXX-PT
WEIGHT			SHEET		REVISION
1.0g			1/1		A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)