





- Specifications :**
- Voltage rating: 250V AC / DC
  - Current rating: 3A AC / DC
  - Withstanding voltage: 800V AC/minute
  - Temperature range: -25°C~+85°C
  - Insulation resistance:  $\geq 1000M\Omega$
  - Contact resistance:  $\leq 20m\Omega$
  - After environmental testing :  $\leq 30m\Omega$

X2581 T F-P SN  
① ② ③ ④ ⑤

- ① Series No.
- ② Category : T-Terminal
- ③ Shape:F-Female
- ④ Material: P-Phosphor bronze ;
- ⑤ Plating Style: SN-Bright Tin Plating (70u")



X2530TF-PSN	Phosphor Bronze	AWG#22-26	1.55mm(Max.)	Stamping Before Plating 30-50u" Ni,70-120u" Sn	X2530H
PART NO	Material	Wire Range	Insulation O. D.	Finish	Used In XKB Housing

广东星坤科技股份有限公司

生效

日期

文件工程章

DSND	DATE	SCALE: N/A	MODEL TYPE: X2530TF-PSN
DWN	DATE	VIEW:	PART NO.: 2.54mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
UNSPECIFIED TOLERANCES			WEIGHT 1.0g
XKB INDUSTRIAL PRECISION CO., LIMITED			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)