


### Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -40°C~+105°C
- Insulation resistance:  $\geq 1000M\ \Omega$
- Contact resistance:  $\leq 10m\ \Omega$
- After environmental testing :  $\leq 20m\ \Omega$

X3025 H M-X X-N2 XX

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category : H-HSG
- ③ Welding Board Angle : M-Male HGS
- ④ Row No., Pin No.: XX-02P~12P
- ⑤ Plug the Pin & special No.
- ⑥ Material : N2-PA66 94V-2
- ⑦ Color : Blank-Natural Color



Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
03	6.00	9.85	08	21.00	24.85
04	9.00	12.85	09	24.00	27.85
05	12.00	15.85	10	27.00	30.85
06	15.00	18.85	11	30.00	33.85
07	18.00	21.85	12	33.00	36.85

X3025HM-XX-N2	Nylon 66 94V-2	X3025TF	X3025W
PART NO	Material	Suitable XKB Terminal	Mates With XKB Wafer

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.heloxkb.com

DSND	DATE	SCALE: NA	MODEL TYPE:
DWNN	DATE	VIEW:	X3025HM-XX-N2
CHKD	DATE	UNIT: mm/in	PART NO.: 3.00 mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)