


- Specifications :**
- Voltage rating: 250V A C / DC
  - Current rating: 5A AC / DC
  - Withstanding voltage: 1000V AC/minute
  - Temperature range: -25°C~+85°C
  - Insulation resistance: ≥1000MΩ
  - Contact resistance: ≤10mΩ
  - After environmental testing : ≤20mΩ

X3025 WR X-2'XX X-N0 XX XX

- ① Series No.
- ② Category : Wafer
- ③ Welding Board Angle: R-90°
- ④ Welding Way : Blank-DIP
- ⑤ Row No.-Pin No. : 2'XX-2'01P~2'12P
- ⑥ Special NO. :
- ⑦ Material : 46-P A46 94V-0
- ⑧ Plating Category: G01-Contact Gold Flash, S1-Bright tin plating
- ⑨ Color : Blank-natural color



Poles	Dimensions (mm)	
	A	B
2'01	---	6.65
2'02	3.00	9.65
2'03	6.00	12.65
2'04	9.00	15.65
2'05	12.00	18.65
2'06	15.00	21.65
2'07	18.00	24.65
2'08	21.00	27.65
2'09	24.00	30.65
2'10	27.00	33.65
2'11	30.00	36.65
2'12	33.00	39.65

Scale 1:3

X3025WR-2'XX-46G01	PA46 UL 94V-0	Brass	Contact Gold	X3025H
X3025WR-2'XX-46SN	PA46 UL 94V-0	Tin-Plated	Tin-Plated	
Part No.	Material	Material(Pin)	Finish(Pin)	Mates With XKB Housing

广东星坤科技股份有限公司

生 日期

發 日期

Δ 文件工程章

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.heloxkb.com

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWNN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)