



Recommended P.C.B. Layout
General Tolerances: 0.05




■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000M Ω
- Contact resistance: ≤10mΩ
- After environmental testing : ≤20mΩ

X3025 WR X-2*XX B-XX XX XX



- ① Series No.
- ② Category : W-wafer
- ③ Welding Board Angle : R-90°
- ④ Welding Way : Blank-DIP
- ⑤ Row No. -Pin No. : 2*XX:2*01P~2*13P
- ⑥ Special NO. : B- without positioning column
- ⑦ Material : 46-PA46 9.4V-0 66-PA66 94V-0 LP-LCP 94V-0
- ⑧ Plating Category : SN-Brigh tin plating
- ⑨ Color : Blank-natural color



Scale 1.3

Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
2*01	---	6.65	2*07	18.00	24.65
2*02	3.00	9.65	2*08	21.00	27.65
2*03	6.00	12.65	2*09	24.00	30.65
2*04	9.00	15.65	2*10	27.00	33.65
2*05	12.00	18.65	2*11	30.00	36.65
2*06	15.00	21.65	2*12	33.00	39.65

X3025WR-2*XX-BLPSN	LCP UL94V-0			
X3025WR-2*XX-B-46SN	Nylon 46 UL94V-0	Brass	Tin-Plated	X3025H
X3025WR-2*XX-B-66SN	Nylon 66 UL94V-0			
Part No.	Material	Material (Pin)	Finish (Pin)	Mates With XHB Housing

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS
www.heloxkb.com

DATE	REVISED	APPROVED	XKB	ANGULAR	±5°
				L ≤ 4	±0.2
				4 < L ≤ 16	±0.3
				16 < L ≤ 63	±0.4
				L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: NA	MODEL TYPE:
DWNN	DATE	VIEW:	X3025WR-2*XX-B-XXSN
CHKD	DATE	UNIT: mm/in	3.00 mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
VXP INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)