


Recommended PCB Layout
General Tolerance ±0.05

Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000MΩ
- Contact resistance: ≤10mΩ
- After environmental testing : ≤20mΩ

X3025 WR X - 2*XX C-XX XX XX

- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨
- Series No.
 - Category : W-wafer
 - Welding Board Angle: R-90°
 - Welding Way: Blank-DIP
 - Row No.-Pin No.: 2*XX-2*01P-2*12P
 - Special NO. : C-The harpoon
 - Material :
46-P A46 94V-0 66-PA66 94V-0 LP-LCP 94V-0
 - Plating Category:
G** Gold-Plated Contact "02-2u"
SN-Bright tin plating 70u"
 - Color : Blank-natural color



Scale 1:3

Poles	Dimensions (mm)	
	A	B
2*01	---	6.65
2*02	3.00	9.65
2*03	6.00	12.65
2*04	9.00	15.65
2*05	12.00	18.65
2*06	15.00	21.65
2*07	18.00	24.65
2*08	21.00	27.65
2*09	24.00	30.65
2*10	27.00	33.65
2*11	30.00	36.65
2*12	33.00	39.65

△ X3025WR-2*XXC-66G02	Nylon 66 UL 94V-0	Brass	Gold Flash	X3025H
X3025WR-2*XXC-LPSN	LCP UL 94V-0		Tin-Plated	
X3025WR-2*XXC-46SN	Nylon 46 UL 94V-0			
X3025WR-2*XXC-66SN	Nylon 66 UL 94V-0			
Part No.	Material	Material (Pm)	Finish(Pm)	Mates With xXB Housing

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS

www.heloxkb.com

DSND	DATE	SCALE: NA	MODEL TYPE:
DWNN	DATE	VIEW:	X3025WR-2*XXC-XXXX
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	3.00 mm Crimp Style Connectors
UNSPECIFIED TOLERANCES			DWG NO.:
XKB	ANGLAR	±5°	
	L ≤ 4	±0.2	
	4 < L ≤ 16	±0.3	
	16 < L ≤ 63	±0.4	
	L > 63	±0.5	

INDUSTRIAL PRECISION CO., LIMITED	WEIGHT	SHEET	REVISION
	1.0g	1/1	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)