



Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: $\geq 1000M\Omega$
- Contact resistance: $\leq 10m\Omega$
- After environmental testing : $\leq 20m\Omega$

X3025 W R S-2*XX C-XX XX XX

(1) (2) (3) (4) (5) (6) (7) (8) (9)

- Series No.
- Category : W-wafer
- Welding Board Angle: R-90°
- Welding Way: S-SMT
- Row No.-Pin No.: 2*XX-Double row
- Special NO.: C-The harpoon
- Material : LP-LCP 94V-0
NO-PA66 94V-0
- Planting Category:
SN-Bright tin plating 70u"
SW-Fog Tin plating
- Color :
Blank-natural color

Poles	Dimensions(mm)		
	A	B	C
2*01	6.65	---	4.20
2*02	8.65	3.00	7.20
2*03	12.65	6.00	10.20
2*04	15.65	9.00	13.20
2*05	18.65	12.00	16.20
2*06	21.65	15.00	19.20
2*07	24.65	18.00	22.20
2*08	27.65	21.00	25.20
2*09	30.65	24.00	28.20
2*10	33.65	27.00	31.20
2*11	36.65	30.00	34.20
2*22	39.65	33.00	37.20

PART NO	Material	Material (pin)	Finish(Pin)	Material (Solder Tabs)	Finish (Solder Tabs)	Mates With Xk/B Housing
X3025WRS-2*XXC-LPSW	LCP UL 94V-0	Brass	Ni 50u"M i/f. Sn 120u/Min.	Brass	Matte Tin Plating	X3025H
X3025WRS-2*XXC-N0SN	PA66 UL 94V-0				Tin-Plated	



广东星坤科技股份有限公司

生 日期
發 日期

文件工程章

REVISIONS
www.heloxb.com

DSND	DATE	SCALE: NA	MODEL TYPE:
DWNN	DATE	VIEW:	X3025WRS-2*XXC-XXXX
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	3.00 mm Crimp Style Connectors
			DWG NO.:
			WEIGHT
			1.0g
			SHEET
			1/1
			REVISION
			A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)