



X3025 WR S- XX D-LP SW XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Category :
W-wafer
Welding Board Angle:
R-90°
- ③ Welding Way:
S-SMT
- ④ Row No.-Pin No.
XX-Single row
- ⑤ Special NO.
- ⑥ D-Solder Tabs
- ⑦ Material :
LP-LCP 94V-0
- ⑧ Planting Category:
V**All Gold-Plated
G**Gold-Plated Contact
*01-Gold Flash ; *02-2U" ; *03-3U" ; *05-5U"
*10-10U" ; *15-15U" ; *30-30U" ; *50-50U"
SN1-Bright tin plating 70U"
SN1-Bright tin plating 120U" Min. ;
SW-Fog Tin plating
- ⑨ Color :
Blank-natural color

Poles	Dimensions		
	A	B	C
2	6.85	3.00	14.20
3	9.85	6.00	17.20
4	12.85	9.00	20.20
5	15.85	12.00	23.20
6	18.85	15.00	26.20
7	21.85	18.00	29.20
8	24.85	21.00	32.20
9	27.85	24.00	35.20
10	30.85	27.00	38.20
11	33.85	30.00	41.20
12	36.85	33.00	44.20

Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000M Ω
- Contact resistance: ≤10m Ω
- After environmental testing : ≤20m Ω
- Mark "*"Indicate Dimensions Need To Controlled In Emphasis

X3025WRS-XXD-LPG15	LCP UL 94V-0	Brass	Contact Area Gold 15u" Min.	Brass	Tin-Plated	X3025H
X3025WRS-XXD-LPSW	LCP UL 94V-0	Brass	Tin Plating Fog	Brass	Tin-Plated	X3025H
PART NO	Material	Material(Pin)	Finish(Pin)	Material (Solder Tabs)	Finish (Solder Tabs)	Mates With XK B Housing

广东星坤科技股份有限公司
P.C.B. LAYOUT

生	日期
效	
文件工程章	
MARK	REVISIONS

DATE	REVISED	APPROVED	DATE	DATE	DATE	DATE	SCALE: N/A	MODEL TYPE: X3025WRS-XXD-LPXXX
							VIEW:	PART NO.:
								3.00 mm Crimp Style Connectors
							UNIT: mm/in	DWG NO.:
							SIZE: A4	
								WEIGHT SHEET REVISION

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)