



P.C.B LAYOUT

X3025 W V X-XX X- XX SN XX

- Series No.
- Category: W-wafer
- Welding Board Angle: V- Straight 180°
- Welding Way: Blank-DIP
- Row No.-Pin No.: XX-02P-12P
- Plug the Pin & Special No.:
- Material: 46-PA46 94V- N0-PA9T 94V-0; XKB 66-PA66 94V-0
- Plating Category: SN-Bright tin plating
- Color: Blank-Natural Color

Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1500V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000M Ω
- Contact resistance: ≤10mΩ XKB
- After environmental testing : ≤20mΩ

Poles	Dimensions(mm)		
	A	B	C
02	3.00	9.65	9.00
03	6.00	12.65	12.00
04	9.00	15.65	15.00
05	12.00	18.65	18.00
06	15.00	21.65	21.00
07	18.00	24.65	24.00
08	21.00	27.65	27.00
09	24.00	30.65	30.00
10	27.00	33.65	33.00
11	30.00	36.65	36.00
12	33.00	39.65	39.00

X3025WV-XX-66SN	PA66 UL 94V-0			
X3025WV-XX-46SNP	A46 UL 94V-0	Brass	Tin-Plated	X3025H
X3025WV-XX-N0SNP	A9T UL 94V-0			
PART NO	Material	Material(Pin)	Finish(Pin)	Mate s With XKB Housing

广东星坤科技股份有限公司

生	日期
发	
Δ	
文件工程章	

REVISIONS

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

www.heloxb.com

DSND	DATE	SCALE: NA	MODEL TYPE:
DWNN	DATE	VIEW:	X3025WV-X X-XXSN
CHKD	DATE	UNIT: mm/in	PART NO.: 3.00mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)