



## Specifications

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: ≥1000M Ω
- Contact resistance: ≤10mΩ
- After environmental testing : ≤20mΩ

### X3025W V X-XXC-XXSNXX

- ① Series No.
- ② Category :  
W-wafer  
Welding Board Angle:  
V-180°  
Welding Way:  
Blank-DIP
- ③ Row No.-Pin No.  
XX-Single row
- ④ Special NO.  
C-With a harpoon
- ⑤ Material :  
LP-LCP 94V-0 66-PA66 94V-0
- ⑥ Planting Category:  
V\*\* : All Gold-Plated  
G\*\* : Gold-Plated Contact  
\*01-Gold Flash ; \*02-2u" ; \*03-3u" ; \*05-5u"  
\*10-10u" ; \*15-15u" ; \*30-30u" ; \*50-50u"  
SN-Bright tin plating 70u"  
SN1-Bright tin plating 120u" Min. ;  
SW-Fog Tin plating
- ⑦ Color :  
Blank-natural color

Poles	Dimensions (mm)	
	A	B
2	3.00	9.65
3	6.00	12.65
4	9.00	15.65
5	12.00	18.65
6	15.00	21.65
7	18.00	24.65
8	21.00	27.65
9	24.00	30.65
10	27.00	33.65
11	30.00	36.65
12	33.00	39.65

X3025WV-XXC-66SN	PA66 UL 94V-0	Brass	Tin-Plated	X3025H
X3025WV-XXC-LPSN	LCP UL 94V-0			
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With XKB Housing

广东星坤科技股份有限公司  
2-2 [0.085]

生	日期
发	

文件工程章	REVISIONS	DATE	REVISED	APPROVED

XKB	ANGULAR	±5°
	L ≤ 4	±0.2
	4 < L ≤ 16	±0.3
	16 < L ≤ 63	±0.4
	L > 63	±0.5

DSND	DATE	SCALE: N/A	MODEL TYPE: X3025WV-XXC-XXSN
DWVN	DATE	VIEW: ④	PART NO.:
CHKD	DATE	UNIT: mm/in	3.00 mm Crimp Style Connectors
APPD	DATE	SIZE: A4	DWG NO.:
UNSPECIFIED TOLERANCES			WEIGHT
INDUSTRIAL PRECISION CO., LIMITED			SHEET
			REVISION
			1.0g
			1/1
			A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)