



P.C.B. LAY OUT



■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 5A AC / DC
- Withstanding voltage: 1000V AC/minute
- Temperature range: -25°C ~ +85°C
- Insulation resistance: ≥1000M Ω
- Contact resistance: ≤10mΩ
- After environmental testing : ≤20mΩ
- Mark ***Indicate Dimensions Need To Controlled In Emphasis

X3025 W V S XX C-XX XX XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪ ⑫

- ① Series No.
- ② Category :
- ③ Wires for
- ④ Welding Board Angle: V-180°
- ⑤ Welding Way: S-SMT
- ⑥ Row No.-Pin No. XX-Single row
- ⑦ Special I/O: C-The hollow
- ⑧ Material: LP-LCP 94V-0 66-PA66 94V-0
- ⑨ Plating Category: V** All Gold-Plated G** Gold-Plated Contact *01-Gold Flash ; *02-2U" ; *03-3U" ; *05-5U" *10-10U" ; *15-15U" ; *30-30U" ; *50-50U"
- ⑩ SW-Bright tin plating 10U"
- ⑪ SN1-Bright tin plating 120U"Min ; SW-Fog Tin plating
- ⑫ Color: Blank-natural color

Poles	Dimensions (mm)		
	A	B	C
02	6.85	3.00	7.30
03	9.85	6.00	10.30
04	12.85	9.00	13.30
05	15.85	12.00	16.30
06	18.85	15.00	19.30
07	21.85	18.00	22.30
08	24.85	21.00	25.30
09	27.85	24.00	28.30
10	30.85	27.00	31.30
11	33.85	30.00	34.30
12	36.85	33.00	37.30

X3025 WVS-XXC-LPSW	LCP UL 94V-0	Brass	Tin Plating Fog	Brass	Tin-Plated	X3025H
X3025WVS-XXC-66SN	PA66 UL 94V-0	Brass	Tin-Plated	Brass	Tin-Plated	X3025H
PART NO	Material	Material (pin)	Finish(Pin)	Material (Solder Tabs)	Finish (Solder Tabs)	Mates With XKB Housing

广东星坤科技股份有限公司

生 日期

文件工程章

REVISIONS
www.heloxkb.com

	XKB	ANGLR	±5°
		L ≤ 4	±0.2
		4 < L ≤ 16	±0.3
		16 < L ≤ 63	±0.4
		L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: NA	MODEL TYPE:
DWN	DATE	VIEW:	X3025WVS-XXC-XXXX
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	3.00 mm Crimp Style Connectors
			DWG NO.:
			WEIGHT
			1.0g
			SHEET
			1/1
			REVISION
			A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)