


Specifications(规格):
 Voltage rating(额定电压):500V AC/DC
 Current rating(额定电流):2A AC/DC
 Withstanding voltage(耐压值):1500V AC/minute
 Temperature range(工作温度):-40℃~+85℃
 Insulation resistance(绝缘电阻):1000MΩ
 Contact resistance(接触电阻):<30mΩ
 After environmental testing(环境测试后):≤40mΩ

X3700T X-P SN X-X
 ○○○○○ ○○○○

- ① 系列
- ② 类别: T-端子
- ③ 外观形态: 空码-普通脚
- ④ 材质: P-磷铜
- ⑤ 电镀类别: G**-镀金 V**-镀全金
 *01-Gold Flash *02-2u" *03-3u" *05-5u"
 *10-10u" *15-15u" *30-30u" *50-50u"
 SN1-镀亮锡(70-120u") SN1-镀亮锡(120u"/Min.)
 0-素材 SW-镀雾锡
- ⑥ 电镀方式:空码-先冲后镀
- ⑦ 型号/MARK及特殊码:



| | | | | | |
|------------|-----------------|------------|---|--------|------------------------|
| X3700T-PSN | Phosphor Bronze | AWG 26-28 | 0.7mm(Max) Stamping Before Plating 30u" | X3700H | |
| PART NO | Material | Wire Range | Insulation O.D | Finish | Suitable Xi/B Terminal |

广东星坤科技股份有限公司

| | |
|----|----|
| 生 | 日期 |
| 发 | |
| 日期 | |

文件工程章

REVISIONS

| DATE | REVISED | APPROVED |
|------|---------|----------|
| | | |

www.xkpcb.com www.hellixib.com www.hellixib.com

| | | | |
|------------------------|------|--------------|-----------------------------|
| DSND | DATE | SCALE: N/A | MODEL TYPE: X3700T-PSN |
| DWNN | DATE | VIEW: | PART NO.: |
| CHKD | DATE | UNIT: mm/mIn | 3.70mm BTB Style Connectors |
| APPD | DATE | SIZE: A4 | DWG NO.: |
| UNSPECIFIED TOLERANCES | | | WEIGHT |
| ANGULAR ±5° | | | SHEET |
| L ≤ 4 ±0.2 | | | REVISION |
| 4 < L ≤ 16 ±0.3 | | | 1.0g |
| 16 < L ≤ 63 ±0.4 | | | 1/1 |
| L > 63 ±0.5 | | | A0 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)