

A

B

C

D

E

F

A



B

C



D

E

F




- Specifications :
- Voltage rating: 250V AC / DC
 - Current rating: 10A AC / DC
 - Withstanding voltage: 1500V AC/minute
 - Temperature range: -25°C~+85°C
 - Insulation resistance: ≥1000MΩ
 - Contact resistance: ≤10mΩ
 - After environmental testing: ≤20mΩ



X5050 W R X-04S X-XX SN XX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No
② Category: W-WAFER
③ Welding Board Angle: R-90°
④ Welding Way: Blank-DIP
⑤ Row No.-Pin No.: XX-Single Row
⑥ Special No: S-With Positioning Column
⑦ Material: N0-PA66 94V-0 ; N2-PA66 94V-2
⑧ Plating Category: SN-Bright Tin Plating
⑨ Color : Blank-Natural Color



Recommended P.C.B Layout
General Tolerance±0.05

X5050WR-04S-N0SN	Nylon 66 UL 94V-0	Brass	Tin-Plated	X5050H
X5050WR-04S-N2SNBK	Nylon 66 UL 94V-2 Black			
X5050WR-04S-N2SN	Nylon 66 UL 94V-2			
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With XKB Housing

For and on behalf of
XKB INDUSTRIAL PRECISION CO., LIMITED
香港星坤工業精密有限公司

△ X					ANGULAR	±5°
△ X					L ≤ 4	±0.2
△ X					4 < L ≤ 16	±0.3
MARK	DESCRIPTION	DATE	REVISED	APPROVED	16 < L ≤ 63	±0.4
					L > 63	±0.5
					UNSPECIFIED TOLERANCES	

DSND		DATE		SCALE: N/A	MODEL TYPE:		
DWN		DATE		VIEW: 	X5050WR-04S-XXSN		
CHKD		DATE		UNIT: mm	PART NO.:		
APPD		DATE		SIZE: A4	5.08mm Crimp Style Connectors		
					DWG NO.:		
XKB INDUSTRIAL PRECISION CO.,LIMITED					WEIGHT	SHEET	REVISION
					1.0g	1/1	A0

XKB INDUSTRIAL PRECISION CO., LIMITED

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)