



Recommended P.C.B

Layout (±0.05)

XXB Connectivity

Technical Data
 Pin(outer sleeve):Brass,machined CuZn38Pb2
 Clip(Contact 6 Finger):Beryllium copper,heat treated
 Insulator:PPS UL94V-0 colour:black
 Current rating:3Amps
 Mating pin Ø:0.635/0.889mm
 Forces (polished steel gauge)Ø0.66mm)
 -Insertion:1.2N typ
 -Withdrawal:0.6N typ
 Mechanical life:min 500cycles
 Contact resistance:max 10m Ω
 Dielectric strength:min 1000V RMS
 Operating temperature:-40°C to+105°C
 Soldering temperature:+255°C

XXB Connectivity

X5511 F V-XX-C70 D30-1000

- ①
- ②
- ③
- ④
- ⑤
- ⑥
- ⑦

- ① Series.N0.
- ② Category : F-Female
- ③ Welding Board Angle : V-Straight 180°
- ④ Row No-Pin No:XX-01P-XXP
- ⑤ Plastic Height :C=7.0mm
- ⑥ Pin Length :D=3.0mm
- ⑦ 1000:TYPE 1000

XXB Connectivity

X5511FV-XX-C70D30-1000	PPS 94V-0	Brass	Tin Gold 1u"	X5511F
PART NO	Material	Material(Terminal)	Finish(Terminal)	Mates With XKB Pin Header

广东星坤科技股份有限公司
 生 日期
 文件工程章
 REVISIONS
 DATE REVISED APPROVED
 www.xxkb.com www.hellixkb.cn

ANGLAR	±5°	DSND		DATE		SCALE: N/A	MODEL TYPE:	
L ≤ 4	±0.2	DWN		DATE		VIEW:	PART NO.:	
4 < L ≤ 16	±0.3	CHKD		DATE		UNIT: mm/in	DWG NO.:	
16 < L ≤ 63	±0.4	APPD		DATE		SIZE: A4	X5511FV-XX-C70D30-1000	
L > 63	±0.5						WEIGHT SHEET REVISION	
UNSPECIFIED TOLERANCES							VXP INDUSTRIAL PRECISION CO., LIMITED	1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)